




Hex Collars

To fit Ditch Witch™ Machines

Fig.	Description	Suitable for machine type	Version
	JT 920 SW47 l= 122 mm	JT 920	octagonal with TCI - wear protection
			with cutting teeth
	JT 1720 - JT 2720 SW64 l= 160 mm (Typ I) l= 122 mm (Typ II)	JT 1720 für EZ- Connect Typ I / Typ II	octagonal with TCI - wear protection
			with cutting teeth
	JT 2720M1 SW70 l= 140 mm	JT 2720M1	octagonal with TCI - wear protection
			with cutting teeth
	JT 3020M1 SW70 l= 170 mm	JT 3020M1	octagonal with TCI - wear protection
			octagonal with TCI - wear protection
	JT 4020 SW80 l= 124 mm	JT 4020	with cutting teeth
			octagonal with TCI - wear protection
	JT 4020M1 SW80 l= 152 mm	JT 4020M1	with cutting teeth
			octagonal with TCI - wear protection

To fit Vermeer™ Machines

Fig.	Description	Suitable for machine type	Version
	D7x11 SW51 l= 110 mm	D7x11, D10x14	hexagonal Standard short
			hexagonal with TCI - wear protection with cutting teeth
	D16x20 D20x22 D24x33 D24x40 D33x44 D36x50 SW64 l= 180 mm	D16x20 D20x22 D24x33 D24x40 D33x44 D36x50	hexagonal with TCI - wear protection (Vermeer)
			hexagonal with TCI - wear protection (AT-Boretac) with cutting teeth
	D24x40, D33x44 D36x50 SW70	D24x40, D33x44 D36x50	octagonal for Starterrod reinforced
			D24x40 II- D36x50 II WS67